

Description	Value
Product name:	UP 15-10 SU7P/TLC, 1 Comfort valve
Product Number:	00595916
EAN number:	5700394894807
Technical:	
Speed Number:	1
Max flow:	6.16 US gpm
Head max:	5.25 ft
	3.28 ft
Maximum operating pressure:	145 psi
Approvals on nameplate:	UL, CSA
Materials:	
Pump housing:	Stainless steel
Impeller:	PES Composite (30% glass-filled)
Installation:	
Maximum ambient temperature:	104 °F
Ambient max at 176°F liquid:	176 °F
Maximum operating pressure:	145 psi
Flange standard:	USA Threaded
Pipe connection:	NPT 3/4"
Pressure stage:	10
Port-to-port length:	5 1/8 in
Liquid:	
Liquid temperature range:	35.6 .. 150.8 °F
Electrical data:	
Number of poles:	2
Max. power input:	25 W
Rated power - P2:	0.04 HP
Main frequency:	60 Hz
Rated voltage:	1 x 115 V
Current in speed 3:	0.23 A
Capacitor size - run:	2 µF/400 V
Insulation class (IEC 85):	F
Motor protection:	CONTACT
Thermal protec:	internal
Type of cable plug:	NEMA 5-15P
Controls:	
Pos term box:	9H
Others:	
Gross weight:	5.51 lb

