

Closet Bolt Cover Cap and Base



Patent Pending



Taller cap eliminates the need to cut brass bolts

- Cap screws onto base for a secure connection
- Base creates a tight seal that helps create a sanitary seal between cap base and china
- Can be installed on new and existing toilets
- Can be used with both 1/4" and 5/16" bolts, maximum length 21/2"
- Boss on base prevents spinning during installation or removal



440-2W




Never cut brass bolts again. Bolts that are cut may become too short to reuse if additional flooring is added.



Base is installed between the bowl and nut.



Cap screws onto base for a secure connection.



Item No.	Description	Min. Qty.	Case Qty.	List Price
BULK				
440-2W	Cover cap and base, white with 425-PB closet bolts, 2/bag	1	25	2.60 EA
442-2W	Cover cap and base, white, 2/bag	1	25	1.65 EA
INDIVIDUALLY BAR-CODED				
440-2WPK	Cover cap and base, white with 425-PB closet bolts, 2/bag	10	10	2.75 EA
442-2WPK	Cover cap and base, white, 2/bag	1	1	2.00 EA







Sioux Chief Toilet Specialties

Raise-A-Ring®

Flange Extension Ring



Build up existing flange when added subfloor, tile, etc. leaves flange at or below floor level. Ring is 7/16" thick, can be stacked if needed.

Ringer Stainless Steel Ring



Fits securely over damaged flanges. Perfect for repairs to damaged closet flanges, or new concrete floor installations.

Plumb Perfect[™]

Closet Bolt



Dome Nut 420



Combination nut and cap. Appliance white. Cannot be knocked off.




Open Nut 425




For use with bolt caps. Fits ½" sockets.



Wedge-It[™] Multi-Purpose Stability Wedge



Scored for easy separation when needed.





Ideal for leveling unsteady closet bowls.

For more information on these toilet specialties see our catalog.

DISTRIBUTED BY

tel: 1-800-821-3944 fax: 1-800-758-5950 www.siouxchief.com P.O. Box 397 24110 South Peculiar Drive Peculiar, Missouri 64078 USA

