# **DWV PIPE HANGER**

## 553 series

### SPECIFICATION

Sioux Chief's 553 series Hangs Tuff™ DWV pipe hanger shall be used where necessary to secure Schedule 40 DWV piping according to all national code requirements. Hanger shall be 100% corrosion proof and UV resistant. Hanger shall be impact resistant to 0°F, and be able to withstand temperatures up to 140°F.

Hangs Tuff<sup>™</sup>

Hanger shall have two preloaded nails, which shall be rust resistant, zinc plated yellow irradiate. Preloaded nails shall have a continuous ring shank to provide a more permanent installation.

Hanger shall feature I-beam design for strength and rigidity with a locking finger device that is designed to hold the pipe in place when installed at all angles.

#### MATERIALS

*hanger*: ABS, U.V. resistant, corrosion-proof, impact-resistant *nail*: 15%" rust-resistant, zinc-coated, yellow irradite, continuous ringshank

#### SAFE WORKING LOAD


	<u>1½</u> "	2"	3"	4"
cradle:	40 lbs.	50 lbs.	45 lbs.	40 lbs.
inverted:	15 lbs.	15 lbs.	15 lbs.	15 lbs.

#### DIMENSIONS

	11⁄2"	2"	3"	4"
A: Length to center of pipe	85⁄8"	815/16"	91⁄16"	915/16"
B: Length of hanger	10"	101/2"	113⁄4"	123⁄8"
C: Length to gripping finger	71⁄2"	71⁄2"	71⁄2"	71/2"
D: Distance between nailways	1"	1"	1"	1"

Item # Submitted
Job Name
Location
Engineer
Contractor
PO# TAG





Create Item N	umber
---------------	-------

## 553-<u>A B</u>

e.g. 553-8W = white 3" Sch. 40 Hangs Tuff

- A
   PIPE SIZE

   □
   6
   1½" Sch. 40

   □
   7
   2" Sch. 40

   □
   8
   3" Sch. 40

   □
   830
   3" Sch. 30\*
- □ 830 3" Sch. 30
- □ 9 4" Sch. 40

<u>B</u> COLOR

- W white
- □ \_ (blank) black
- \* 3" Sch. 30 only available in white. (553-830W)

Sioux Chief