STANDARD ALARMS

For Sump, Sewage and Effluent



A Family and Employee Owned Company

ALM-Series

- Indoor rated
- 115V Operation with 9-volt battery backup
- 86 Decibel horn
- Red LED alarm ring
- Green power "ON" light
- Auxiliary contacts

Models

ALM-2-1

ALM-2

ALM-P1

ALM-PK

- Automatic alarm reset
- Alarm Test / Silence buttons
- 9-volt battery included

See ALM-EYE Series literature for Wi-Fi connected models

Patent: See LibertyPumps.com/patents

application)



ther ty Pumps

ALM-Series Pump Alarm

Liberty Pumps

Narrow Angle Compact Snap-on Float Switch Float Switch (Sewage/Effluent Fits 1-1/4" or 1-1/2" pipe (Sump application)



Puddle Sensor (For floor level sensing)



ALM-2W & ALM-230W

Indoor/Outdoor ALM-2W - 115V ALM-230W - 230V

- Meets Enclosure Type **3**R Standards
- 115V Operation, direct wire
- Thermoplastic enclosure
- Red alarm beacon

Narrow angle float switch, 10' cord

Narrow angle float switch, 20' cord Compact snap-on float switch, 10' cord

Puddle sensor, 50' cord

- 82 Decibel horn
- Alarm Test / Silence switch
- 20' Float switch cord
- Includes auxiliary contacts
- Easy field wiring with removable cover



ALM-3W

Commercial Outdoor

- NEMA 4X rated
- Commercial-duty enclosure
- 115V Operation, direct wire
- Flashing red alarm LEDs
- 95 Decibel horn
- Alarm "Test / ON / Silence" switch
- 20' Float switch cord
- Includes auxiliary contacts

Copyright © Liberty Pumps, Inc. 2022 All rights reserved. LLIT006639-R12/22

Liberty Pumps - 7000 Apple Tree Avenue - Bergen, New York 14416 Phone 800-543-2550 - Fax 585-494-1839 - www.LibertyPumps.com