



PROLINE® HIGH CAPACITY ATMOSPHERIC VENT



Highest Recoveries

- Capacity/input combinations up to 98 gallons/75,000 BTU's to produce recoveries up to 81 gallons per hour.

Fully Automatic Controls with Safety Shutoff

- Accurate, dependable control system requires no electrical connections.
- Fixed automatic gas shutoff device for added safety.

Green Choice® Gas Burner

- Patented eco-friendly burner design reduces NOx emissions up to 33% and complies with Low-NOx emission requirements of 40 ng/l.

Dynaclean™ Diffuser Dip Tube

Coregard™ Anode Rod

Push-Button Piezo Ignitor

Blue Diamond® Glass Coating

Enhanced-Flow Brass Drain Valve

Code Compliance

- Meets UBC, CEC and ICC National Codes.
- Meets the thermal efficiency and standby loss requirements of the U.S. Department of Energy and current edition of ASHRAE/IES 90.1.

CSA Certified and ASME Rated T&P Relief Valve

Maximum Hydrostatic Working Pressure 150 psi

Design-Certified By CSA International

- Certified at 300 psi test pressure and 150 psi working pressure. Listed according to ANSI Z21.10.1-CSA 4.1 standards governing storage tank-type gas water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Nominal Capacity	BTU Input Natural Gas	Recovery @ 90°F Rise Gallon Per Hour	Dimensions in Inches				Approx. Shipping Weight (lbs)
				Height to Top of Draft Hood	Height to Top of Tank	Diameter	Draft Hood	
FCG-75	74	75,100	81	61	58-1/2	16	4	270
FCG-100	98	75,100	81	68-1/2	66-1/2	16	4	340

*Recover rating based on 81% thermal efficiency.

**Recover rating based on 80% thermal efficiency.

†The GCN-75 comes standard with side loop fittings for use with hydronic heating applications.