



PROLINE® XE HIGH EFFICIENCY NON-CONDENSING POWER VENT



Versatile Power Vent Design

- All models feature an exclusive 3-position rotatable blower outlet which adds flexibility.
- Combined horizontal and vertical vent runs up to 180 equivalent feet with 4" diameter venting (ABS, PVC, CPVC and polypropylene).
- All models are equipped with a protected sensor that detects the presence of flammable vapors and automatically disables the burner to prevent ignition.
- Air intake snorkel elevates the inlet location of combustion air to prevent flammable vapors from entering the sealed combustion chamber.

Hot-surface Ignitor

- More robust and reliable than standing pilot, and reduces energy consumption

ENERGY STAR® Qualified

- All models (except GPVX 75L) meet the ENERGY STAR® requirement and may also qualify for local utility and rebate programs.
- Built-in heat traps on the water inlet and outlet reduce the amount of heat lost through piping
- 2-inch, thick, "Environmentally-Friendly" foam insulation reduces the amount of heat loss and contributes to overall energy efficiency

User-Friendly

- State-of-the-art electronic gas control provides more precise temperature control.
- LED control light displays operation status and diagnostics information.

Enhanced-Flow Brass Drain Valve

Available in Natural Gas and Propane

Design-Listed by CSA International

- Certified at 300 psi test pressure and 150 psi working pressure.
- Listed according to ANSI Z21.10.1-CSA 4.1 or ANSI Z21.10.3-CSA 4.3 standards governing storage tank-type water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Series	Nominal Capacity	Rated Storage Volume	UEF	Recovery @ 90°F Rise Gallon Per Hour	BTU Input Gallon Per Hour	First Hour Rating (Gallons)	Dimensions in Inches			Approx. Shipping Weight (lb)
								Height to Top of Blower	Height to Top of Tank	Diameter	
GPVL-40	200	40	38	0.67	45	40,000	72	59	49-5/8	22	174
GPVT-40	200	40	38	0.70	56	50,000	93	68-1/2	59-1/4	20	176
GPVL-50	200	50	49	0.72	45	40,000	93	60-1/8	50-3/4	24	198
GPVT-50	200	50	48	0.72	56	50,000	96	68-1/8	58-3/4	22	192
GPVX-50L	200	50	50	0.73	69	62,000	108	61-1/8	52	24	212
†GPVX-75L	210	75	72	0.69	80	76,000	N/A	70-5/8	61-1/4	26	277

Natural gas models cited are series 200/210. Propane models 201/211.
 Side connections are standard on GPVX models.
 For side connect models, add "L" to the model number (example: GPVT-40L).
 All models rated for installation at altitudes up to 10,100 ft.
 † GPVX-75L is not ENERGY STAR® Qualified.