

Hot Water Where You Need It

Point-of-Use Electric Mini-Tank Water Heaters

Bosch Tronic 3000 T Series

Models ES8, ES4, ES2.5

Note: All Tronic 3000 T models are sold in the U.S. only.



BOSCH

Invented for life



The Bosch Tronic 3000 T point-of-use electric mini-tanks are available in three sizes which can be wall-hung (bracket included) or floor-mounted and come with a temperature/pressure relief valve. Simply tap into the cold water line, provide electrical connection and install the water heater directly at the sink to provide hot water. They may also be installed inline near the point-of-use to eliminate waiting for hot water from the primary source.

Features

- ▶ Supplies up to 2 sinks at a time (ES8 model)
- ▶ Provides hot water quickly at point-of-use
- ▶ Compact, lightweight, space saving
- ▶ Units can be wall / floor mounted (bracket included) with multi-directional mounting available (ES8 model only)
- ▶ Temperature / pressure relief valve included
- ▶ Glass-lined tank for long service life
- ▶ Models ES2.5 and ES4 have a simple 120 VAC plug-in connection
- ▶ 6 year limited warranty[§]



Common Applications

- ▶ Sink located far from water heater
- ▶ Kitchenettes
- ▶ In-law suites
- ▶ Half bathroom or powder room

[§] Copies of original warranties in their entirety are available at www.boschheatingandcooling.com

Bosch Tronic 3000 T

Point-of-Use Electric Mini-Tank Water Heaters

Easy Installation

Simply tap into the cold water line, provide electrical connection and install the water heater directly at the sink. Can be used alone to provide a small volume of water or installed inline with a central water heater near the point-of-use to eliminate the wait for hot water.



Technical Specifications	ES8	ES4	ES2.5
Part Number	7738004998	7738004997	7738004996
Thermal Efficiency	98%	98%	98%
Tank Volume (gal)	7	4	2.7
Heating Capacity, Watts	1440	1440	1440
Recovery Rate @ 90°F Rise, GPH	6.8	6.8	6.8
Temperature Range (°F)	65 - 145	65 - 145	65 - 145
Max Operating Pressure (psi)	150	150	150
Weight (lbs)	29.5	17.3	15.5
Dimensions (in)	17½ x 17½ x 14½	13¾ x 13¾ x 13½	13¾ x 13¾ x 10¾
Water Fittings	¾" Male NPT	½" Male NPT	½" Male NPT
Relief Valve	Included	Installed	Installed
Electrical Requirements			
Volts (VAC)	120	120	120
Amps	12	12	12
Connection Type	Hard Wired	Plug-In	Plug-In

Note: All Tronic 3000 T models are sold in the U.S. only.

No more waiting for hot water. Ideal for stand-alone use or recirculation systems.



Relief valve is required; however it is not shown in above photo for clarity.

Bosch Thermotechnology Corp.

Londonderry, NH • Ft. Lauderdale, FL
 General Inquiries: 1-866-642-3198
www.boschheatingandcooling.com

73H991002c 07-15

Copyright © 2015 Bosch Thermotechnology Corp.
 All rights reserved. Subject to change without notice.