

Brass Ball Valves Cross-Reference by Manufacturer

Valve Type, by Connections	Wright Valves	Everhot	WATTS	NIBCO	Milwaukee Valve	Matco-Norca	Apollo
Threaded (FPT x FPT)	BVT		FBV-3C, FBV-4	T-FP-600A	BA-475B	757, 759	64, 77F-100
Threaded (FPT x FPT), Lead-Free	BVT-LF		LFFBV-3C, LFFBV-4	T-FP-600A-LF	PM01LF	757LF, 759LF	77FLF-100
Threaded (FPT x FPT) w/ Waste Port	BVT-D						
Threaded (FPT x FPT) w/ Waste Port, Lead-Free				T-FP-600-AD-LF			
Sweat (CxC)	BVS		FBVS-3C, FBVS-4	S-FP-600A	BA-485B	757, 759	64, 77F-200
Sweat (CxC), Lead-Free	BVS-LF		LFFBVS-3C, LFFBVS-4	S-FP-600A-LF	PM11LF	757LF, 759LF	77FLF-200
Sweat (CxC) w/ Waste Port	BVS-D			S-FP-600-AD			
Sweat (CxC) w/ Waste Port, Lead-Free				S-FP-600-AD-LF			
PEX x PEX Ball Valves		VPP	FBV-PEX, WPBV	PXCP400		754PX	
PEX x PEX (Lead-Free)		VPP-LF	LFFBV-PEX, LFWPBV	PXCP400-LF		754PXLF	94XLF

Ball valves shall have the following specifications:

- 2-Piece Body
- Lead-Free Models Must Meet 2014 SDWA, NSF/ANSI 372, NSF/ASNI 61-G
- 600 WOG, 150 WSP Pressure Rated for Threaded/Sweat and 400 WOG Rated for PEX
- Full Port (Full Flow) Design
- ANSI Compliant Solder/Threaded Ends or ASTM F1807 Compliant PEX Ends
- Chrome Plated Brass Ball
- 1/4-Turn Steel Handle

See actual product specifications for a complete list of materials, standards, ratings, approvals and compatible applications.