For Residential and Commercial Applications Job Name Engineer / Architect Job Location Wholesaler Submittal Date Contractor

CSSB 3/4" ID (7/8" OD) Coated Gas Appliance Connectors

Use: For use with indoor and outdoor connections of gas appliances to gas piping system. May be used with natural, manufactured, mixed and liquefied petroleum (LP or propane) gases, and LP gas-air mixtures.

Design Features:

- Superior corrosion resistance to harsh chemicals found in common household cleaning, plumbing repair, and masonry products
- UV rays & salt resistant, ProCoat® connectors are certified for indoor & outdoor use
- Greater strength & flexibility with greater depth & number of corrugations to withstand greater torque & bend cycles
- Outperforms industry standards for torsion (1.5X) without compromising the integrity of the coating or connector
- Outperforms industry standard for repeated bending (2X) without compromising the integrity of the coating or connector
- **Smoother, burnished flare** on connector ends seal with less torque
- Uniform coat over entire length of connector for complete corrosion resistance of the stainless steel core
- 100% Leak tested







-40° - 150° F Temperature: Pressure: 1/2 PSI maximum

| CONNECTOR FLOW CAPACITY (Straight Length) | | | | | | | | | |
|-------------------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|--|
| 12" 18" 24" 30" 36" 48" 60" | | | | | | | | 72" | |
| BTU per Hour (NG) | 290,900 | 290,900 | 290,900 | 270,500 | 255,900 | 215,000 | 197,400 | 173,900 | |
| BTU per Hour (LPG) | 465,440 | 465,440 | 465,440 | 432,800 | 409,440 | 344,000 | 315,840 | 278,240 | |
| Watts per Hour (NG) | 85,254 | 85,254 | 85,254 | 79,276 | 74,997 | 63,010 | 57,852 | 50,965 | |

| MATERIAL SPECIFICATIONS | | | | | |
|-------------------------------|---------------|--|--|--|--|
| Tubing Stainless steel | | | | | |
| Coating | Polymer blend | | | | |
| Nuts | Steel | | | | |
| Fittings | Steel | | | | |

This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.




CSSB 3/4" ID (7/8" OD) Coated Gas Appliance Connectors

| Part | Listing: | |
|------|-------------|----------------------------------------------------------------------------------------|
| | CSSB1212-24 | 3/4" ID (7/8" OD) with 1" MIP x 1" MIP fittings x 24" length |
| | CSSB1412-12 | 3/4" ID (7/8" OD) with 1" FIP x 1" MIP fittings x 12" length |
| | CSSB1412-18 | 3/4" ID (7/8" OD) with 1" FIP x 1" MIP fittings x 18" length |
| | CSSB1412-24 | 3/4" ID (7/8" OD) with 1" FIP x 1" MIP fittings x 24" length |
| | CSSB1412-36 | 3/4" ID (7/8" OD) with 1" FIP x 1" MIP fittings x 36" length |
| | CSSB1412-48 | 3/4" ID (7/8" OD) with 1" FIP x 1" MIP fittings x 48" length |
| | CSSB11-12 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 12" length |
| | CSSB11-18 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 18" length |
| | CSSB11-24 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 24" length |
| | CSSB11-30 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 30" length |
| | CSSB11-36 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 36" length |
| | CSSB11-48 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 48" length |
| | CSSB11-60 | 3/4" ID (7/8" OD) with 3/4" MIP x 3/4" MIP fittings x 60" length |
| | CSSB21-12 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 12" length |
| | CSSB21-18 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 18" length |
| | CSSB21-24 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 24" length |
| | CSSB21-24 P | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 24" length, bagged |
| | CSSB21-24 X | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 24" length, bagged with cut case |
| | CSSB21-30 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 30" length |
| | CSSB21-36 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 36" length |
| | CSSB21-36 P | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 36" length, bagged |
| | CSSB21-36 X | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 36" length, bagged with cut case |
| | CSSB21-48 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 48" length |
| | CSSB21-60 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 60" length |
| | CSSB21-72 | 3/4" ID (7/8" OD) with 3/4" FIP x 3/4" MIP fittings x 72" length |
| | CSSB22-12 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 12" length |
| | CSSB22-18 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 18" length |
| | CSSB22-24 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 24" length |
| | CSSB22-30 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 30" length |
| | CSSB22-36 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 36" length |
| | CSSB22-48 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 48" length |
| | CSSB22-60 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 60" length |
| | CSSB22-72 | 3/4 "ID (7/8" OD) with 3/4" FIP x 3/4" FIP fittings x 72" length |
| | | |



CSSB 3/4" ID (7/8" OD) Coated Gas Appliance Connectors



| PART DIMENSIONS (Inches) | | | | | | | | | |
|-------------------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| Connector Length – Nut by Nut | | | | | | | | | |
| Series | DIM. | 12" | 18" | 24" | 30" | 36" | 48" | 60" | 72" |
| CSSB | Α | 10.00 | 16.00 | 22.00 | 28.00 | 34.00 | 46.00 | 58.00 | 70.00 |

| PART DIMENSIONS (Inches) | | | | | | | | | | |
|-----------------------------------|------|---------|---------|---------|---------|---------|---------|---------|---------|--|
| Connector Lengths - with Fittings | | | | | | | | | | |
| Model | DIM. | 12" | 18" | 24" | 30" | 36" | 48" | 60" | 72" | |
| CSSB1412 | В | 12.00 / | 18.00 / | 24.00 / | 30.00 / | 36.00 / | 48.00 / | 60.00 / | 72.00 / | |
| C33B1412 | Ь | 14.00 | 20.00 | 26.00 | 32.00 | 38.00 | 50.00 | 62.00 | 74.00 | |
| CSSB21 | В | 12.00 / | 18.00 / | 24.00 / | 30.00 / | 36.00 / | 48.00 / | 60.00 / | 72.00 / | |
| | | 14.00 | 20.00 | 26.00 | 32.00 | 38.00 | 50.00 | 62.00 | 74.00 | |
| CSSB22 | В | 12.00 / | 18.00 / | 24.00 / | 30.00 / | 36.00 / | 48.00 / | 60.00 / | 72.00 / | |
| | | 14.00 | 20.00 | 26.00 | 32.00 | 38.00 | 50.00 | 62.00 | 74.00 | |
| CSSB11 | В | 12.00 / | 18.00 / | 24.00 / | 30.00 / | 36.00 / | 48.00 / | 60.00 / | 72.00 / | |
| | | 14.00 | 20.00 | 26.00 | 32.00 | 38.00 | 50.00 | 62.00 | 74.00 | |

Listings & Certifications:

- CSA listed to ANSI Z21.24 / CSA 6.10 standard "Connectors for Gas Appliances" (file #204593)
- CSA listed to ANSI Z21.75 / CSA 6.27 standard "Connectors for Outdoor Gas Appliances & Manufactured Homes" (file #204593)
- The Commonwealth of Massachusetts





