Liberty Pumps[®]

GR-Series

Guide Rail System

Features:

- 2" or 3" discharge FNPT
- Heavy cast iron construction
- Rugged one rail design with auto-guide feature
- 1-1/4" guide pipe FNPT (guide rail pipe not included)
- Heavy duty nitrile sealing grommet
 - Upper cast iron rail support bracket provided
 - Powder coated for corrosion resistance

2" Models:

GR22-FL fits FL100, FL150 and FL200-Series Pumps

GR22-LE fits LE70, LE100, LEH100, LEH150 and LEH200-Series Pumps GR22-S fits LE40, LE50-Series Pumps 3" Models:

GR30 fits LE70, LE100, LEH100, LEH150 and LEH200-Series Pumps

innovate. evolve.

GR-Series Guide Rails

Specifications and Dimensional Data

Material: Class 25 Gray Cast Iron Weight: GR22 – 38 lbs. GR30 – 46 lbs.

Seal: Heavy Duty Nitrile
Rail Size: 11/4" (Not Included)

Discharge: GR22 - 2" Female NPT, GR30 - 3" Female NPT

Maximum Pump Weight: 250 lbs.


Upper Rail Support: Class 25 Gray Cast Iron

Rail Support Bolts: Stainless Steel

MODELS:	DISCHARGE	SERIES
*GR22-FL	2"	FL100, FL150, FL200
*GR22-LE	2"	LE70, LE100, LEH100, LEH150, LEH200
GR22-S	2"	LE40, LE50
GR30	3"	LE70, LE100, LEH100, LEH150, LEH200

^{*2&}quot; internal female thread on pump mating claw allows for mounting to other pump makes





1/2-13 UNC

THREADED STUDS


5.50" STUD


SPAÇING

-2.06"

GR22 - 2"

Dimensional Data





Specifications are subject to change without notice.