

PVC Ball Valves Cross-Reference by Manufacturer

Valve Description	Matco-Norca	NIBCO	Hayward	Spears	Homewerks (EPDM Seat)
1/2", Solvent Weld (Socket)	770S03	MA064A6	QV1T050SE	19757	
3/4", Solvent Weld (Socket)	770S04	MA064A8	QV1T075SE	19758	
1", Solvent Weld (Socket)	770S05	MA064AA	QV1T100SE	19759	
1-1/4", Solvent Weld (Socket)	770S06	MA064AB	QV1T125SE	19760	
1-1/2", Solvent Weld (Socket)	770S07	MA064AC	QV1T150SE	19762	
2", Solvent Weld (Socket)	770S08	MA064AD	QV1T200SE	19763	
1/2", FIP Threaded	770T03	MA065A6	QV1T050TE	19764	VBV-P40-B3B
3/4", FIP Threaded	770T04	MA065A8	QV1T075TE	19765	VBV-P40-B4B
1", FIP Threaded	770T05	MA065AA	QV1T100TE	19766	VBV-P40-B5B
1-1/4", FIP Threaded	770T06	MA065AB	QV1T125TE	19767	VBV-P40-B6B
1-1/2", FIP Threaded	770T07	MA065AC	QV1T150TE	19768	VBV-P40-B7B
2", FIP Threaded	770T08	MA065AD	QV1T200TE	19769	VBV-P40-B8B

Ball valves shall have the following specifications:

- PVC Body (white or gray)
- EPDM O-Ring
- PTFE Seat Seal (Except Spears)
- 150 PSI Pressure Rating (125 PSI for Spears) @ 73°F (70°F for Hayward) Non-Shock
- NSF Listed (Except Hayward)
- 1/4-Turn Handle

See actual product specifications for a complete list of materials, standards, ratings, approvals and compatible applications.