

CABLE TIES

554 series

SPECIFICATION

Sioux Chief cable ties shall be used to organize CTS tube or bundles of tubing (i.e. PEX) pipe. Primarily for indoor use.

Mounting cable ties shall be used to secure bundles to walls studs or other surfaces easily. Mounting cable ties accepts #10 screws. Cable ties shall be made from Nylon 66, ultraviolet black material to resist harmful light rays.

MATERIALS

Nylon 66, ultraviolet black (UVB), UL94 V2 flame rating

FAILURE LOAD

8" and 14" models: 50 lbs.

21" and 36" models: 175 lbs.

TEMPERATURE RATINGS

maximum operating temperature: 185°F

minimum operating temperatures: -40°F

melting point: 400°F

DIMENSIONS

	8" model	14" model	21" model	36" model
width	3/16"	3/16"	5/16"	5/16"
maximum bundle diameter	2"	4"	6"	11"

Item # Submitted _____
Job Name _____
Location _____
Engineer _____
Contractor _____
PO# _____ TAG _____



554-08



554-608

Create Item Number

554- A B

e.g. 554-614 = 14" mounting cable tie

A MOUNTING

- _ none
- 6* includes mounting piece

* Only available on 8" and 14" models

B LENGTH

- 08 8"
- 14 14½"
- 21 21"
- 36 36"