### Webstone

**VALVE INNOVATION** 

THE ONLY WAY TO INSTALL ANY TANKLESS WATER HEATER

PATENTED TECHNOLOGY







### THE ORIGINAL TANKLESS WATER HEATER SERVICE VALVES

- Heavy duty forged brass valves with full port main flow channel & drain
- Hi-flow full port 3/4" drain offers the greatest flow rate
- 304 Stainless steel wing handle for easy actuation of the main ball
- Color coded insulator rings for easy identification of hot & cold valves
- Aluminum handle for easy actuation of the drain ball
- Available in threaded or sweat connections
- Available with or without a pressure relief valve
- Available with lead-free CleanBrass construction for compliance with AB1953, NSF/ANSI 61-G & NSF 372
- GUARANTEED FOR LIFE

### PATENTED TECHNOLOGY

Hot & Cold Set of Full w/ Hi-Flow Hose Drain	_	e Relief Valve Outlet & A	djustabl	le Packing Glan	ds				NFORMS T 600	WOG · ISO	
	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	Α	В	С	D	E	F	G
IPS UNION × IPS	40443	40443W	3/4"	1/8	3/4	4 15/16	1 1/2	1 13/16	2 7/8	3/4	3/4
IPS UNION × SWT	50443	50443W	3/4"	1/8	3/4	4 15/16	1 1/2	1 13/16	2 7/8	3/4	3/4
INCLUDES RESIDENT	IAL PRES	SURE RELIEF VALVE (1	50 PSI/	200,000 BTU)							
IPS UNION × IPS	40443PR	40443WPR	3/4"	1/8	3/4	4 15/16	1 1/2	1 13/16	2 7/8	3/4	3/4
IPS UNION × SWT	50443PR	50443WPR	3/4"	1/8	3/4	4 15/16	1 1/2	1 13/16	2 7/8	3/4	3/4
INCLUDES COMMERC	CIAL PRES	SURE RELIEF VALVE (1	.50 PSI	/ <b>2,703,000 B</b> 1	TU) & 3/4	" CLOSE NIF	PPLE				
INOLODES COMMEN		40443WPR2	3/4"	1/6	3/4	4 15/16	1 1/2	1 13/16	2 7/8	3/4	3/4
IPS UNION × IPS	40443PR2	40443WFK2	0/ 1	-/ -							


### **AVAILABLE AS:**






- CHOICE OF IPS OR SWT EXP TWH SERVICE VALVES
- 200.000 BTU PRESSURE RELIEF VALVE
- 24" × 3/4" GAS FLEX LINE
- 3/4" CGA GAS BALL VALVE

	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G
IPS ISOLATOR® E-X-P™ Complete	40443COM	40443WC0M
SWT ISOLATOR® E-X-P™ Complete	50443COM	50443WC0M





## The ISOLATOR COMPACT VERSION OF OUR ORIGINAL ISOLATOR E-X-P

- Heavy duty forged brass valves with full port main flow channel
- Uniquely designed lever/wing handle for easy actuation of the main ball
- Color coded aluminum handles for easy identification of hot & cold valves
- Large drain port outlets
- Available in threaded & sweat connections
- Available with your choice of three different pressure relief valves
- Available with lead-free CleanBrass construction for compliance with AB1953, NSF/ANSI 61-G & NSF 372
- GUARANTEED FOR LIFE

### PATENTED TECHNOLOGY

		d Brass Ball Valves w/ H djustable Packing Glands		use Diallis,					NFORMS T	,	0 W0G
NCLUDES RESIDENT	IAL PRES	SURE RELIEF VALVE (1	50 PSI/	200,000 BTU)							
	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	Α	В	С	D	E	F	G
PS UNION × IPS	44443PR	44443WPR	3/4"	1/10	3/4	4 1/4	1 5/8	2 5/8	2 3/4	3/4	1/2
ra union x ira	44444PR	44444WPR	1"	1/10	1	5	2 3/8	2 3/8	2 3/4	3/4	3/4
IPS UNION × SWT	54443PR	54443WPR	3/4"	1/10	3/4	4 3/4	1 5/8	2 5/8	2 3/4	3/4	1/2
	54444PR	54444WPR	1"	1/10	1	5 1/8	2 3/8	2 3/8	2 3/4	3/4	3/4
NCLUDES RESIDENT	IAL PRES	SURE RELIEF VALVE (30	PSI/5	10,000 BTU)							
IDE IINION ~ IDE	44443PR3	44443WPR3	3/4"	1/10	3/4	4 1/4	1 5/8	2 5/8	2 3/4	3/4	1/2
S UNION × IPS	44444PR3	44444WPR3	1"	1/10	1	5	2 3/8	2 3/8	2 3/4	3/4	3/4
PS UNION × SWT	54443PR3	54443WPR3	3/4"	1/10	3/4	4 3/4	1 5/8	2 5/8	2 3/4	3/4	1/2
IPS UNION × SWI	54444PR3	54444WPR3	1"	1/10	1	5 1/8	2 3/8	2 3/8	2 3/4	3/4	3/4
NCLUDES COMMER	CIAL PRES	SURE RELIEF VALVE (1	.50 PSI/	/2,703,000 B1	TU) & 3/4	" CLOSE NI	PPLE				
IPS UNION × IPS	44443PR2	44443WPR2	3/4"	1/6	3/4	4 1/4	1 5/8	2 5/8	2 3/4	3/4	1/2
IFS UNIUN X IPS	44444PR2	44444WPR2	1"	1/6	1	5	2 3/8	2 3/8	2 3/4	3/4	3/4
	54443PR2	54443WPR2	3/4"	1/6	3/4	4 3/4	1 5/8	2 5/8	2 3/4	3/4	1/2
IPS UNION × SWT											

### **AVAILABLE AS:**






- CHOICE OF IPS OR SWT E2 TWH SERVICE VALVES
- 200,000 BTU PRESSURE RELIEF VALVE
- 24" × 3/4" GAS FLEX LINE
- 3/4" CGA GAS BALL VALVE

	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G
IPS ISOLATOR® E-X-P™ E2 Complete	44443COM	44443WCOM
SWT ISOLATOR® E-X-P™ E2 Complete	54443COM	54443WCOM





# The **ISOLATOR**®

COMPACT VERSION OF OUR ORIGINAL ISOLATOR E-X-P

## WITH AN ADJUSTABLE PRESSURE RELIEF VALVE OUTLET

- Adjustable pressure relief valve fitting for use with pipe covers & recessed boxes
- Heavy duty forged brass valves with full port main flow channel
- Uniquely designed lever/wing handle for easy actuation of the main ball
- Color coded aluminum handles for easy identification of hot & cold valves
- Large drain port outlets
- Available in threaded & sweat connections
- Available with your choice of three different pressure relief valves
- Available with lead-free CleanBrass construction for compliance with AB1953, NSF/ANSI 61-G & NSF 372
- GUARANTEED FOR LIFE

### **PATENTED TECHNOLOGY**

INCLUDES RESIDENT	TAL PRES	SURE RELIEF VALVE (1	50 PSI/	200,000 BTU)								
	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	Α	B (COLD)	B (HOT)	С	D	E	F	G
IPS UNION × IPS	45443PR	45443WPR	3/4"	1/10	3/4	4 1/4	5 7/8	1 5/8	2 5/8	2 3/4	3/4	1/2
IPS UNION × SWT	55443PR	55443WPR	3/4"	1/10	3/4	4 3/4	6 3/8	1 5/8	2 5/8	2 3/4	3/4	1/2
INCLUDES RESIDENT	IAL PRES	SURE RELIEF VALVE (30	PSI/5	10,000 BTU)								
IPS UNION × IPS	45443PR3	45443WPR3	3/4"	1/10	3/4	4 1/4	5 7/8	1 5/8	2 5/8	2 3/4	3/4	1/2
IPS UNION × SWT	55443PR3	55443WPR3	3/4"	1/10	3/4	4 3/4	6 3/8	1 5/8	2 5/8	2 3/4	3/4	1/2
INCLUDES COMMER	CIAL PRES	SURE RELIEF VALVE (1	.50 PSI	/2,703,000 B1	TU) & 3/4	" CLOSE NII	PPLE					
IPS UNION × IPS	45443PR2	45443WPR2	3/4"	1/6	3/4	4 1/4	5 7/8	1 5/8	2 5/8	2 3/4	3/4	1/2
IPS UNION × SWT	55443PR2	55443WPR2	3/4"	1/6	3/4	4 3/4	6 3/8	1 5/8	2 5/8	2 3/4	3/4	1/2


### **AVAILABLE AS:**





- **CHOICE OF IPS OR SWT E3 TWH SERVICE VALVES**
- **200.000 BTU PRESSURE RELIEF VALVE**
- 24" × 3/4" GAS FLEX LINE
- 3/4" CGA GAS BALL VALVE

	ITEM #	LEAD-FREE ITEM # CERTIFIED TO NSF/ANSI 61-G
IPS ISOLATOR® E-X-P™ E3 Complete	45443COM	45443WCOM
SWT ISOLATOR® E-X-P™ E3 Complete	55443COM	55443WC0M





Available with lead-free CleanBrass construction for compliance with AB1953, NSF/ANSI 61-G & NSF 372


	NO.	DESCRIPTION	MATERIAL	_	c		RESIDENTIAL PRESSURE RELIEF VALVE
	1	BODY	BRASS				•
	2	SEATS	PTFE				
	3	BALL	BRASS HCP			lcl	! <b> </b>
	4	HANDLE NUT	STAINLESS STEEL			13	
	5	WING STYLE "T" HANDLE	STEEL CP				
	6	HANDLE JACKET	VINYL				
	7	PACKING GLAND	BRASS		e i 🎥 👖		+ F +
	8	STEM SEAL	PTFE				
	9	STEM	BRASS				COMMERCIAL PRESSURE
-	10	END CAP	BRASS	B			RELIEF VALVE & 3/4" CLOSE NIPPLE
	11	UNION NUT	BRASS				
	12	RETAINING RING	STAINLESS STEEL				
	13	UNION FITTING	BRASS	<b>3</b>			] [>
	14	WASHER	EPDM				
	15	DRAIN VALVE HANDLE	ENAMEL COATED ALUMINUM			6	+
	16	DRAIN VALVE HANDLE SCREW	BRASS	$\cup$	A		Ė   ) ~
	17	CAP & STRAP	BRASS W/ EPDM HOSE WASHER	!			<del>'</del>
	18	RELOCATION ADAPTER (HOT)	BRASS	E			← F →
				DRAIN	нот	COLD	




### **ADVANTAGES**

- Quicker, consistent quality installation
- Fewer leak paths
- Allows for easy cleaning or flushing of system
- Allows for one person diagnostic testing of water heater unit
- GUARANTEED FOR LIFE


### **NORMAL OPERATION**



### **CLEANING**



### **FLUSHING**



### ISOLATOR® E-X-P™ ACCESSORIES AVAILABLE TO MAKE YOUR JOB EASIER





FITS	ITEM #	LEAD FREE ITEM# CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	WT/CASE
EXP	28003	-	3/4"	1/100	85
E2	28023	28023W	3/4"	1/100	55



### 1/2" UNION ADAPTER KITS Use these kits to change the inlet connection of your service valves from 3/4" to 1/2"

FITS	ITEM #	LEAD FREE ITEM# CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	WT/CASE
ALL MODELS	29032	29032W	3/4" × 1/2"	BULK	BULK

PRESSURE RELIEF VALVES					
RESIDENTIAL PRESSURE RELIE	F VALVES				
	ITEM #	LEAD FREE ITEM# CERTIFIED TO NSF/ANSI 61-G	SIZE	CTN/CASE	WT/CASE
150 PSI/200,000 BTU	20713	20713W	3/4"	1/100	49
30 PSI/510,000 BTU	20733	-	3/4"	1/100	49
COMMERCIAL PRESSURE RELI	EF VALVES	(Requires close nipple # 2	9003)		
150 PSI/2.7 MILLION BTU	20723	-	3/4"	1/24	31
CLOSE NIPPLE	29003	_	3/4"	BIII K	RIII K

